

## **Q11 Electric shearing**

## **FEATURES**:

- Single-side open-type mechanical down driving system with safety stability, compact construction, ease of operation and modern appearance.
- Equipped with rotary-key clutch, it can be sensitive operated with low noise, low maintenance and long service life.
- With low cutting angle and inclined shear direction, bowing and twist of the material is kept to a minimum.
- Adjustable butterfly-spring hold-down device for minimum displacement of sheet-plate so cutting precision is ensured.
- Easily operated gear shaft back gauge with scale works great for shearing in batches.

Model No.	Q11 4X2000	Q11 4X2500	Q11 4X3200	Q11 6X2000	Q11 6X2500
Item No.	C2241	C2242	C2243	C2261	C2262
Specifications					
Shearing thickness	4 mm	4 mm	4 mm	6 mm	6 mm
Shearing width (mm)	2000 mm	2500 mm	3200 mm	2000 mm	2500 mm
Shearing angle (°)	1°30′	1°30′	1°18′	1°45′	1°45′
Strokes per minute	56	56	56	56	56
Back gauge range (mm)	0~500 mm				
Motor (kw)	5.5 kw	5.5 kw	7.5 kw	7.5 kw	7.5 kw
Net Weight (kg)	3300 kg	3600 kg	4800 kg	4100 kg	4500 kg