



## Q35Y-25 HYDRAULIC IRON WORKER

### FEATURES:

- They adopt hydraulic driving system and they are the latest iron workers in our country, Various metal plate, squarebar, round bar, angle, channel and joist can be cut, punched and notched on the machine. It is also equipped with a stop device for cutting.

Model No.	Q35Y-12	Q35Y-15	Q35Y-16	Q35Y-20
<b>Specifications</b>				
Pressure(Ton)	45	55	60	90
Max.cutting thickness(mm)	12	15	16	20
Plate strength(N/mm )	≤450	≤450	≤450	≤450
Cutting angle(degree)	7°	7°	7°	8°
Sheraing size of one stroke(mm)	12x250	15x300	16x250 8x400	20x330 10x480
Ram stroke(mm)	60	60	80	80
Number of strokes(cpm)	8	8	8	8
Throat depth(mm)	200	200	300	355
Punching thickness(mm)	12	15	16	20
Max. Punching diameter(mm)	22	24	25	30
Power of main motor(kw)	3	4	4	5.5
Overall dimensions L x W x H(mm)	1200x520x1500	1320x590x1620	1640x730x1770	1860x800x1900
Weight of machine(kg)	1000	1400	1600	2500

Model No.	Q35Y-25	Q35Y-30	Q35Y-40	
<b>Specifications</b>				
Pressure(Ton)	110	140	200	
Max.cutting thickness(mm)	25	30	40	
Plate strength(N/mm )	≤450	≤450	≤450	
Cutting angle(degree)	7°	7°	7°	
Sheraing size of one stroke(mm)	25x330 16x600	30x355 20x600	35x400 25x700	
Ram stroke(mm)	80	80	100	
Number of strokes(cpm)	6	6	8-25	
Throat depth(mm)	400	600	600	
Punching thickness(mm)	25	26	35	
Max. Punching diameter(mm)	35	38	41	
Power of main motor(kw)	7.5	11	15	

Overall dimensions L x W x H(mm)	2355x960x2090	2680x1040x2300	2850x1300x2400	
Weight of machine(kg)	4500	6800	9500	