

Catalogo JPG TOOLS Maquinaria Industrial

RBM30HV Round bending machine

Features:

The round bending machine can be combined with various mold wheels in order to meet various processing demands.

Horizontal and vertical operation

With standard foot pedal

The Round bending machine features an electric three-roller-wheel structure.

It has the advantage of a two axis drive. The upper axis can be moved up and down to adjust the diameter of the processed work piece.

It can conduct round bending processing for plates, T-shaped materials and so on.

The round bending machine has a standard roller wheel, of which the front two types of roller wheel can be used both vertically and horizontally.

The reversible pedal switch facilitates the operation.

Main Technical data

Model Dia. Of roller Power Spindle speed Packing size N.W./G.W.		RBM30HV 30mm 0.75kw/1HP 9r/min 120x75x121cm 244/282kgs					
				Capacity	Size	Min dia.(mm)	Article No.
					40x40x3	1000	One set standard roller
					50x15	350	
				5 5	50x30x3	1200	
				•	⊄15 ⊄20 ⊄25 ⊄30	600	HV30-15-4
	40X40X2 40X40X3 40X40X4 X40X40X5	400	HV30-15-5				
	40X40X2 40X40X3 40X40X4 40X40X5	400	HV30-15-6				

	50X50X2 50X50X3 50X50X4 50X50X5	400	HV30-15-7
	50X25X2 50X25X3	300	HV30-15-8
	50X25X4 50X25X5 50X25X2 50X25X3	400	LIN/20 4E 0
	50X25X4 50X25X5	400	HV30-15-9
	50X25X2 50X25X3 50X25X4 50X25X5	300	HV30-15-10
0 0		1000	HV30-15-11