



WC67Y-30X1320 Hydraulic Press Brake Machine

FEATURES:

- All steel welded structure, stress relieved for high rigidity and stability
- Torsion shaft forced synchronization of mechanical limit stopper balance,with high precision
- Integrated hydraulic transmission system,large range of speed regulation thanks to transmission of the sliding block, stable and reliable performance
- Rear stopper and the sliding block have electrical adjustment for the stroke,with manual fine tuning,and digital indication
- Adjustment mechanism of sliding block independent from oil cylinder assembly to enhance sealing effect of upper punch
retainer is fitted with tilting warp offset mechanism
- For bending machine from 250Tup synchronization mechanism of mechanical or electrical hydraulic transmission is fitted,
lower working table is fitted with warp offset mechanism
- Multi machine combined operation is possible

Model No.	WC67Y 25/1600	WC67Y 25/2000	WC67Y 25/2500	WC67Y 40/2000
Specifications				
Normal Pressure (Kn)	250 kn	250 kn	250 kn	400 kn
Working Table Length(mm)	1600 mm	2000 mm	2500 mm	2000 mm
Distance Between Housing	1190 mm	1590 mm	2090 mm	1590 mm
Throat Depth (mm)	200 mm	200 mm	200 mm	200 mm
Side stroke (mm)	100 mm	100 mm	100 mm	100 mm
Ma.open height (mm)	300 mm	300 mm	300 mm	300 mm
Working Speed	12 mm	12 mm	12 mm	8 mm
Motor Power	3 kw	3 kw	3 kw	5.5 kw
PackingSize(cm)	167x127x180	207x127x180	257x127x180	207x127x180
Model No.	WC67Y 40/2500	WC67Y 50/2500	WC67Y 50/3200	WC67Y 63/2500
Specifications				
Normal Pressure (Kn)	400 kn	500 kn	500 kn	630 kn
Working Table Length(mm)	2500 mm	2500 mm	3200 mm	2500 mm
Distance Between Housing	2090 mm	1900 mm	2600 mm	2050 mm
Throat Depth (mm)	200 mm	250 mm	250 mm	250 mm
Side stroke (mm)	100 mm	120 mm	120 mm	100 mm

Ma.open height (mm)	300 mm	300 mm	300 mm	360 mm
Working Speed	8 mm	8 mm	8 mm	8 mm
Motor Power	5.5 kw	5.5 kw	5.5 kw	5.5 kw
PackingSize(cm)	257x127x180	257x135x196	327x135x196	256x173x228
Model No.	WC67Y 63/3200	WC67Y 80/3200	WC67Y 100/3200	WC67Y 100/4000
Specifications				
Normal Pressure (Kn)	630 kn	800 kn	1000 kn	1000 kn
Working Table Length(mm)	3200 mm	3200 mm	3200 mm	4000 mm
Distance Between Housing	2600 mm	2600 mm	2600 mm	3200 mm
Throat Depth (mm)	250 mm	250 mm	320 mm	320 mm
Side stroke (mm)	100 mm	100 mm	130 mm	130 mm
Ma.open height (mm)	360 mm	360 mm	390 mm	390 mm
Working Speed	8 mm	8 mm	8 mm	8 mm
Motor Power	5.5 kw	7.5 kw	7.5 kw	7.5 kw
PackingSize(cm)	326x173x228	326x181x224	326x125x235	406x125x265
Model No.	WC67Y 125/3200	WC67Y 160/3200	WC67Y 300/5000	
Specifications				
Normal Pressure (Kn)	1250 kn	1600 kn	3000 kn	
Working Table Length(mm)	3200 mm	3200 mm	5000 mm	
Distance Between Housing	2600 mm	2600 mm	4080 mm	
Throat Depth (mm)	320 mm	320 mm	400 mm	
Side stroke (mm)	130 mm	200 mm	250 mm	
Ma.open height (mm)	390 mm	470 mm	560 mm	
Working Speed	8 mm	8 mm	6 mm	
Motor Power	7.5 kw	11 kw	22 kw	
PackingSize(cm)	326x167x240	326x146x264	503x214x344	