



WE67K-200X3200 CNC Press Brake Machine

FEATURES:

- Equipped with Delem control system(made in netherland)(cybeleec could be used also), raster displayer, hydraulic valve, servomotor are all importing products.
- Adopting reliable electro-hydraulic proportional synchronization servo and its parallelism precision could reach 0.02mm It can support eccentric load.
- Ram stroke(Y1, Y2)and back gauge(X,R,Z)are controlled by controller.
- Back gauge is adopted ball-screw and linear guide way, the repeat positioning precision of X is very high and act smartly.

Model No.	WE67K 100/3200	WE67K 100/4000	WE67K 160/3200	WE67K 160/4000
Specifications				
Normal Pressure (Kn)	1000 kn	1000 kn	1600 kn	1600 kn
Working Table Length(mm)	3200 mm	4000 mm	3200 mm	4000 mm
Distance Between Housing	2900 mm	3700 mm	2880 mm	3680 mm
Throat Depth (mm)	320 mm	320 mm	320 mm	320 mm
Ma.open height (mm)	400 mm	400 mm	400 mm	400 mm
Side stroke (mm)	200 mm	200 mm	200 mm	200 mm
Motor Power (kw)	7.5 kw	7.5 kw	11 kw	11 kw
Net Weight (kg)	8100 kg	8300 kg	10500 kg	12000 kg
PackingSize(cm)	345x150x268	420x156x271	345x155x276	425x155x282
Model No.	WE67K 200/3200	WE67K 200/4000	WE67K 250/3200	WE67K 250/4000
Specifications				
Normal Pressure (Kn)	2000 kn	2000 kn	2500 kn	2500 kn
Working Table Length(mm)	3200 mm	4000 mm	3200 mm	4000 mm
Distance Between Housing	2880 mm	3680 mm	2770 mm	3560 mm
Throat Depth (mm)	320 mm	320 mm	400 mm	400 mm
Ma.open height (mm)	400 mm	400 mm	450 mm	450 mm
Side stroke (mm)	200 mm	200 mm	250 mm	250 mm
Motor Power (kw)	15 kw	15 kw	18.5 kw	18.5 kw
Net Weight (kg)	10500 kg	12000 kg	14000 kg	15500 kg
PackingSize(cm)	345x160x276	425x160x282	350x180x350	447x197x335
Model No.	WE67K 300/3200	WE67K 300/4000	WE67K 400/3200	WE67K 400/4000
Specifications				
Normal Pressure (Kn)	3000 kn	3000 kn	4000 kn	4000 kn
Working Table Length(mm)	3200 mm	4000 mm	3200 mm	4000 mm

Distance Between Housing	2760 mm	3560 mm	2750 mm	3550 mm
Throat Depth (mm)	400 mm	400 mm	400 mm	400 mm
Ma.open height (mm)	500 mm	500 mm	500 mm	500 mm
Side stroke (mm)	300 mm	300 mm	300 mm	300 mm
Motor Power (kw)	22 kw	22 kw	30 kw	30 kw
Net Weight (kg)	16500 kg	22000 kg	25000 kg	29800 kg
PackingSize(cm)	356x197x335	460x200x350	360x210x340	460x210x350
Model No.	WE67K 500/4000	WE67K 500/5000	WE67K 500/6000	WE67K 600/5000
Specifications				
Normal Pressure (Kn)	5000 kn	5000 kn	5000 kn	6000 kn
Working Table Length(mm)	4000 mm	5000 mm	6000 mm	5000 mm
Distance Between Housing	3500 mm	4500 mm	4800 mm	4000 mm
Throat Depth (mm)	400 mm	400 mm	400 mm	500 mm
Ma.open height (mm)	630 mm	630 mm	630 mm	630 mm
Side stroke (mm)	320 mm	320 mm	320 mm	320 mm
Motor Power (kw)	37 kw	37 kw	37 kw	37 kw
Net Weight (kg)	40000 kg	45000 kg	45000 kg	50000 kg
PackingSize(cm)	460x218x360	560x218x360	615x362x520	515x382x520

Model No.	WE67K 600/6000	WE67K 650/7000	WE67K 800/5000	WE67K 800/6000
Specifications				
Normal Pressure (Kn)	6000 kn	6500 kn	8000 kn	8000 kn
Working Table Length(mm)	6000 mm	7000 mm	5000 mm	6000 mm
Distance Between Housing	5050 mm	5400 mm	4000 mm	5050 mm
Throat Depth (mm)	450 mm	450 mm	500 mm	500 mm
Ma.open height (mm)	630 mm	650 mm	800 mm	800 mm
Side stroke (mm)	320 mm	350 mm	350 mm	350 mm
Motor Power (kw)	45 kw	45 kw	55 kw	55 kw
Net Weight (kg)	58000 kg	65000 kg	75000 kg	85000 kg
PackingSize(cm)	625x370x490	516x450x530	516x450x530	620x492x580

Model No.	WE67K 1000/6000			
Specifications				
Normal Pressure (Kn)	10000 kn			

Working Table Length(mm)	6000 mm			
Distance Between Housing	5050 mm			
Throat Depth (mm)	500 mm			
Ma.open height (mm)	800 mm			
Side stroke (mm)	400 mm			
Motor Power (kw)	55 kw			
Net Weight (kg)	105000 kg			
PackingSize(cm)	650x494x630			

WE67K CNC HYDRAULIC PRESS BRAKE

FEATURES:

- Equipped with Delem control system(made in netherland)(cybeleec could be used also), raster displayer, hydraulic valve, servomotor are all importing products.
- Adopting reliable electro-hydraulic proportional synchronization servo and its parallelism precision could reach 0.02mm It can support eccentric load.
- Ram stroke(Y1, Y2)and back gauge(X,R,Z)are controlled by controller.
- Back gauge is adopted ball-screw and linear guide way, the repeat positioning precision of X is very high and act smartly.

Model No.	WE67K 100/3200	WE67K 100/4000	WE67K 160/3200	WE67K 160/4000
Specifications				
Normal Pressure (Kn)	1000 kn	1000 kn	1600 kn	1600 kn
Working Table Length(mm)	3200 mm	4000 mm	3200 mm	4000 mm
Distance Between Housing	2900 mm	3700 mm	2880 mm	3680 mm
Throat Depth (mm)	320 mm	320 mm	320 mm	320 mm
Ma.open height (mm)	400 mm	400 mm	400 mm	400 mm
Side stroke (mm)	200 mm	200 mm	200 mm	200 mm
Motor Power (kw)	7.5 kw	7.5 kw	11 kw	11 kw
Net Weight (kg)	8100 kg	8300 kg	10500 kg	12000 kg
PackingSize(cm)	345x150x268	420x156x271	345x155x276	425x155x282
Model No.	WE67K 200/3200	WE67K 200/4000	WE67K 250/3200	WE67K 250/4000
Specifications				
Normal Pressure (Kn)	2000 kn	2000 kn	2500 kn	2500 kn
Working Table Length(mm)	3200 mm	4000 mm	3200 mm	4000 mm
Distance Between Housing	2880 mm	3680 mm	2770 mm	3560 mm

Throat Depth (mm)	320 mm	320 mm	400 mm	400 mm
Ma.open height (mm)	400 mm	400 mm	450 mm	450 mm
Side stroke (mm)	200 mm	200 mm	250 mm	250 mm
Motor Power (kw)	15 kw	15 kw	18.5 kw	18.5 kw
Net Weight (kg)	10500 kg	12000 kg	14000 kg	15500 kg
PackingSize(cm)	345x160x276	425x160x282	350x180x350	447x197x335
Model No.	WE67K 300/3200	WE67K 300/4000	WE67K 400/3200	WE67K 400/4000

Specifications				
Normal Pressure (Kn)	3000 kn	3000 kn	4000 kn	4000 kn
Working Table Length(mm)	3200 mm	4000 mm	3200 mm	4000 mm
Distance Between Housing	2760 mm	3560 mm	2750 mm	3550 mm
Throat Depth (mm)	400 mm	400 mm	400 mm	400 mm
Ma.open height (mm)	500 mm	500 mm	500 mm	500 mm
Side stroke (mm)	300 mm	300 mm	300 mm	300 mm
Motor Power (kw)	22 kw	22 kw	30 kw	30 kw
Net Weight (kg)	16500 kg	22000 kg	25000 kg	29800 kg
PackingSize(cm)	356x197x335	460x200x350	360x210x340	460x210x350

Model No.	WE67K 500/4000	WE67K 500/5000	WE67K 500/6000	WE67K 600/5000
-----------	---------------------------	---------------------------	---------------------------	---------------------------

Specifications				
Normal Pressure (Kn)	5000 kn	5000 kn	5000 kn	6000 kn
Working Table Length(mm)	4000 mm	5000 mm	6000 mm	5000 mm
Distance Between Housing	3500 mm	4500 mm	4800 mm	4000 mm
Throat Depth (mm)	400 mm	400 mm	400 mm	500 mm
Ma.open height (mm)	630 mm	630 mm	630 mm	630 mm
Side stroke (mm)	320 mm	320 mm	320 mm	320 mm
Motor Power (kw)	37 kw	37 kw	37 kw	37 kw
Net Weight (kg)	40000 kg	45000 kg	45000 kg	50000 kg
PackingSize(cm)	460x218x360	560x218x360	615x362x520	515x382x520

Model No.	WE67K 600/6000	WE67K 650/7000	WE67K 800/5000	WE67K 800/6000
-----------	---------------------------	---------------------------	---------------------------	---------------------------

Specifications				
Normal Pressure (Kn)	6000 kn	6500 kn	8000 kn	8000 kn
Working Table Length(mm)	6000 mm	7000 mm	5000 mm	6000 mm
Distance Between Housing	5050 mm	5400 mm	4000 mm	5050 mm
Throat Depth (mm)	450 mm	450 mm	500 mm	500 mm
Ma.open height (mm)	630 mm	650 mm	800 mm	800 mm

Side stroke (mm)	320 mm	350 mm	350 mm	350 mm
Motor Power (kw)	45 kw	45 kw	55 kw	55 kw
Net Weight (kg)	58000 kg	65000 kg	75000 kg	85000 kg
PackingSize(cm)	625x370x490	516x450x530	516x450x530	620x492x580

Model No.	WE67K 1000/6000			
Specifications				
Normal Pressure (Kn)	10000 kn			
Working Table Length(mm)	6000 mm			
Distance Between Housing	5050 mm			
Throat Depth (mm)	500 mm			
Ma.open height (mm)	800 mm			
Side stroke (mm)	400 mm			
Motor Power (kw)	55 kw			
Net Weight (kg)	105000 kg			
PackingSize(cm)	650x494x630			