

XL6032V Horizontal Knee Type Milling

Horizontal knee-type milling machine



Driven by AC servo motor .
 Table automatic feed on X.Y.Z
 Automatic rapid feed X.Y.Z
 XL6032C:table travel(x axis)1100mm
 XL6032CL: table travel (x axis):1300mm

Standard accessories:
 Reduction sleeve,wrenches,Parallel vise, mill chuck, work lamp, coolant system, chip tray, horizontal cutter arbors.

Optional:
 DRO, 58PCS clamping kit, mill chuck set, H/V rotary table, universal dividing head,vertical milling head & milling adjustable hanging unit

Specification	Unit	XL6032	XL6032C	XL6032CL
Spindle taper		7:24 ISO50	7:24 ISO50	7:24 ISO50
Distance between spindle nose and table surface	mm	20-480	20-470	20-470
Distance from spindle axis to arm	mm	175	175	175
Spindle speed range		60-1800r.p.m (12steps)	60-1800r.p.m (12steps)	60-1800r.p.m (12steps)
Table size	mm	1325x320	1325x320	1600x320
Table travel(X,Y,Z)	mm	750/320/460	1100/320/450	1300/320/450
T-slots(NO/width/pitch)	mm	3/18/70	3/18/70	3/18/70
Arm travel	mm	500	500	500
Main motor power	kw	5.5	5.5	5.5
3 to feed AC servo motor torque	Nm	10	10	10
Overall size	mm	1800x2100x1870	2245x2100x1870	2520x2100x1870
Net weight	kg	2400	2465	2510