



## XW6032A Horizontal Knee Milling

*Table size 1320\*320mm*

*Table travel 800\*300mm*

<b>SPECIFICATION</b>	UNIT	XW6032A
TABLE SIZE	MM	1320x320
SPINDLE TAPER		ISO50
SPINDLE SPEED RANGE	R/MIN	58-1800
TABLE TRAVEL	MM	800(750)x300
DISTANCE FROM SPINDLE AXIS TO TABLE SURFACE	MM	0-400
DISTANCE BETWEEN SPINDLE AXIS AND BOOM	MM	175
MAIN MOTOR	KW	4
OVERALL DIMENSION(LxWxH)	MM	2070x1900x1850
NET WEIGHT	KG	2100

## Horizontal knee-type milling machine



XW6032A



XW6036B



XW6136



Swivel table(optional)

Rectangular table guideways with high stability.  
Hardened and ground table surface  
Automatic feed on X.Y axis,motorized lifting and lowering of table on Z axis

XW6032A: table travel 800\*300mm

XW6032B: table travel 1000\*300mm

XW6136:table travel 1000\*300mm,table swivel 45 degree.

### Standard accessories:

Reduction sleeve,wrenches,work lamp, coolant system, horizontal cutter arbors.vertical milling head & milling adjustable hanging unit

### Optional:

3-axis DRO, 58PCS clamping kit, mill chuck set(15), H/V rotary table. universal dividing head,

Specification	Unit	XW6032A	XW6032B	XW6136
Table size	mm	1320 × 320	1320 × 320	1320 × 360
Spindle taper		ISO50	ISO50	ISO50(H), ISO40(V)
Spindle speed ( steps )	rpm	58–1800	58–1800	58–1800 ( 12 )
Table travel	mm	800 × 300	1000 × 300	1000 × 300
Distance between spindle axis and table surface	mm	0–400	0–400	0–400
Distance between spindle axis and ram surface	mm	175	175	175
Main motor	Kw	4	4	4
Overall dimension (L × W × H)	mm	2070 × 1900 × 1850	2070 × 2020 × 1850	2070 × 2050 × 1950
Machine weight	kg	2100	2200	2300