



XW6032B Horizontal Knee Milling

TABLE TRAVEL 1000*300MM

SPECIFICATION	UNIT	XW6032B
TABLE SIZE	MM	1320x320
SPINDLE TAPER		ISO50
SPINDLE SPEED RANGE	R/MIN	58-1800
TABLE TRAVEL	MM	1000x300(MANUAL)
NO./WIDTH/DISTANCE OF T-SLOT	MM	5-14-63
DISTANCE FROM SPINDLE AXIS TO TABLE SURFACE	MM	0-400
DISTANCE BETWEEN SPINDLE AXIS AND BOOM	MM	175
MAIN MOTOR	KW	4
OVERALL DIMENSION(LxWxH)	MM	2070x2020x1850
NET WEIGHT		

Horizontal knee-type milling machine



XW6032A



XW6036B



XW6136



Swivel table(optional)

Rectangular table guideways with high stability.
 Hardened and ground table surface
 Automatic feed on X.Y axis,motorized lifting and lowering of table on Z axis
 XW6032A: table travel 800*300mm
 XW6032B: table travel 1000*300mm
 XW6136:table travel 1000*300mm,table swivel 45 degree.

Standard accessories:

Reduction sleeve,wrenches,work lamp, coolant system, horizontal cutter arbors.vertical milling head & milling adjustable hanging unit

Optional:

3-axis DRO, 58PCS clamping kit, mill chuck set(15), H/V rotary table, universal dividing head,

Specification	Unit	XW6032A	XW6032B	XW6136
Table size	mm	1320 × 320	1320 × 320	1320 × 360
Spindle taper		ISO50	ISO50	ISO50(H), ISO40(V)
Spindle speed (steps)	rpm	58–1800	58–1800	58–1800 (12)
Table travel	mm	800 × 300	1000 × 300	1000 × 300
Distance between spindle axis and table surface	mm	0–400	0–400	0–400
Distance between spindle axis and ram surface	mm	175	175	175
Main motor	Kw	4	4	4
Overall dimension (L × W × H)	mm	2070 × 1900 × 1850	2070 × 2020 × 1850	2070 × 2050 × 1950
Machine weight	kg	2100	2200	2300