



X6128C Milling machine

| Specification | X6128A | X6128C |
|---|----------------|----------------|
| Table size | 1200x280 | 1200x280 |
| Table travel(Z.Y.Z) | 620/260/400 | 620/260/400 |
| T-slots(NO:/width/pitch) | 5/14/50 | 5/14/50 |
| Spindle speed range | 12 45~1350 | 12 45~1350 |
| Spindle taper | 7:24 IS040 | 7:24 IS040 |
| Table feed (Z.Y.Z) | 8 13~265 | 8 32~840 |
| Table feed (Z) | 9~270 | 9~270 |
| Distance between spindle axis table surface | 110~510 | 110~510 |
| Distance between horizontal spindle and tam | 150 | 150 |
| Atm travel | 550 | 550 |
| Main motor power | 3 | 3 |
| Rapid motor power | 0.75 | 0.75 |
| Cooling pump flow | 12 | 12 |
| Overall size | 1725x1450x1750 | 1725x1450x1750 |
| N.W.kg | 1350 | 1380 |



Milling machine



Hardened and ground guide-ways.

X6128A:Table automatic feed on X.Y. direction by gear driven.

X6128C:Table automatic feed on X.Y.Z direction by gear driven.

Standard accessories:

Draw bar, reduction sleeve. wrenchs, parallel vise. mill chuck,worklamp. coolant system, chip tray, horizontal cutter arbor.

Optional accessories:

DRO,58pcs clamping kit, milling chuck set, vertical milling head, universal dividing head, H/V rotary table

| Specification | Unit | X6128A | X6128C |
|--|--------|-----------------|-----------------|
| Table size | mm | 1200x280 | 1200x280 |
| T-slots(NO/width/pitch) | | 5 / 14 / 50 | 5 / 14 / 50 |
| Table travel(X,Y,Z) | mm | 620 / 260 / 400 | 620 / 260 / 400 |
| Spindle speed range | r/min | 45-1350(12step) | 45-1350(12step) |
| Spindle taper | | ISO40 | ISO40 |
| Table feed(X,Y) | mm/min | 13-265(8step) | 30-855(8step) |
| Table feed(Z) | mm/min | manual | 9-270(8step) |
| Distance between horizontal spinde and ram surface | mm | 150 | 150 |
| Distance between horizontal spinde and table surface | mm | 135-535 | 110-510 |
| Mian motor power | kw | 3 | 3 |
| Overall size | mm | 1750x1450x1750 | 1750x1450x1750 |
| Net weight | kg | 1350 | 1380 |