

X6328B Milling machine

Milling machine



X6328A

X6328C

X6328B

Harden and ground guideways.

X6328B: Table automatic feed on X.Y.Z direction by gear driven.3HP Taiwan High speed milling head,Table can be swivel $\pm 45^\circ$ (OPTIONAL)

X6328A:Table automatic feed on X.Y. direction by gear driven.

X6328C:Table automatic feed on X.Y.Z direction by gear driven.

Standard accessories:

draw bar, spindle rod, reduction sleeve, wrenches,
Parallel vice, mill chuck,drill chuck, work lamp, coolant
system, titled wedge,horizontal cutter arbors

Optional accessories:

DRO, universal dividing head, rotary table,
58PCS clamping kit, mill chuck set, swivel work
table,"CE" spindle protecting arbor

Specitication	Unit	X6328A	X6328C	X6328B
Table size	mm	1200x280	1200x280	1200x280
T-slots(No./width/pitch)		5/14/50	5/14/50	5/14/50
Table travel(X,Y,Z)	mm	620/260/400	620/260/400	620/260/400
Spindle nose to table surface	mm	115-515	90-490	90-490
Distance between horizontal spindle and table surface		0-330	0-305	0-305
Spindle speed range	r/min	115-1750(V)45-1350(H)	115-1750(V) 45-1350(H)	60-4200(V) 45-1350(H)
Spindle taper		MT4(V) ISO40(H)	MT4(V) ISO40(H)	R8/ISO40(V) ISO40(H)
Table feed(X.Y)	mm/min	13-265(8 step)	30-855(8 step)	30-855(8 step)
Table feed(Z)	mm/min	-	9-270	9-270
Distance between horizontal spindle and ram surface	mm	215	215	215
Main motor power	kw	0.85/1.5(V) 2.2(H)	0.85/1.5(V) 2.2(H)	3HP(V) 3kw(H)
Rapaid motor power	kw	0.75	0.75	0.75
Overall dimensions	mm	1750x1450x2150	1750x1450x2150	1750x1450x2150
Net weight	kg	1380	1420	1600