



XZX6350C Milling Drilling Machine

Model No	Units	XZX6350C	XZ6350A
Max. tapping dia.	mm	M16	M16
Max. drilling capacity	mm	50	50
Max. end milling capacity	mm	25	25
Max. face milling capacity	mm	100	100
Work table size	mm	1120x280	1120x260
T-slot size	mm	14	14
Cross travel	mm	230	270
Longitudinal travel	mm	600	600
Taper of spindle bore		ISO40	ISO40
Spindle stroke	mm	120	120
Distance between spindle to table	mm	110-470	100-400
Range of spindle 3speed(vertical)	rpm	115-1750	115-1750
Range of spindle 3speed(horizontal)	rpm	38-1310	38-1310
Motor(vertical)	Kw	0.85/1.5	0.85/1.5
Motor(horizontal)	Kw	2.2	2.2
Packing size	mm	1580x1330x2250	1655x1450x2150
N.W.	Kg	1350	1500

Standard accessories

Drill chuck	drawbar	Tapping assembly	Tool box & tools
Halogen work lamp	Milling vise	Coolant system	Chip tray
X axis mechanical automatic feed			

Optional accessories

Keyless drill chuck	58pcs clamping kits	Digital readout	Y,Z-axis automatic feed
Automatic spindle feed			