

## ZX40 drilling milling

<http://www.ycjxie.com> E-Mail: [Sales@ycjxie.com](mailto:Sales@ycjxie.com) [dfzhu@163.net](mailto:dfzhu@163.net)



### Drilling & milling machine ZX45



Max. drilling capacity(Steel, iron)	31.5mm(MT3) 40mm(MT4)
Max. milling capacity(Face, end)	80mm 32mm
Working table size	800x240mm
Working table longitudinal travel	565mm
Working table cross travel	230mm(190mm)
Spindle taper	MT3, MT4 or R8
Spindle stroke	120mm
Spindle speed(rpm)	50HZ:75-1600 60HZ:90-1970
Max distance spindle to table	470mm
Spindle box swivel degree	90°
Power and speed of motor	1.1kw,1450rpm
NW/GW weight	300/350kg(375/400)
Package size	820x760x1150mm

#### Features-ZX45:

Milling, drilling, tapping, boring, reaming, wide and big table. head can be tilted right & left, large square dovetail column.

Milling head up & down by power (option), workable power feed(option).

Micro feed precision, heavy-duty tapered roller bearing spindle,

Positive spindle lock, adjustable gips on table, geared drive, lower noise, accurate position, strong rigidity, strong cutting power.

#### Features-ZX40

- \* Milling, drilling, tapping, boring, reaming.
- \* Head swivels or tilts.
- \* Micro feed precision
- \* Heavy-duty tapered roller bearing spindle.
- \* Positive spindle lock.
- \* Adjustable gips on table.
- \* Geared drive. lower noise.
- \* Accurate position, strong rigidity, strong cutting power.

#### Standard accessories:

Draw bar, adapter, taper shank for drilling chuck, drilling chuck, arbor, T slot bolt, washer, nut, tilted wedge, spanner, oil gun.

#### Optional accessories:

Auto-lifting headstock electrically, auto spindle power down feed, table power feed, swivel work table, spring collect, tapping assembly, double speed motor, number depth gauge, halogen worklamp, coolant pump, 58pcs clamping tool kit, milling chuck set, end milling cutter set, face milling cutter, machine stand and chip tray, milling vice, DRO, H/V rotary table, universal dividing head

Max. drilling capacity(Steel, iron)	31.5mm(MT3) 40mm(MT4)
Max. milling capacity(Face, end)	80mm 32mm
Working table size	730x210mm
Working table longitudinal travel	500mm
Working table cross travel	230mm
Spindle taper	MT3, MT4 or R8
Spindle stroke	120mm
Spindle speed(rpm)	50HZ:75-1600 60HZ:90-1970
Max distance spindle to table	470mm
Spindle box swivel degree	360°
Head tilt left right	90°
Power and speed of motor	1.1kw,1450rpm
NW/GW weight	270/300kg
Package size	820x760x1150mm

