

## ZX50C Milling drilling machine

### Milling drilling machine



ZX50C (heavy type)



ZX50F (heavy type)



Light type: with swivel table & steel sheet machine stand

Hardened and ground table surface, headstock can swivel  $\pm 45^\circ$  (left-right)  
 ZX50C: vertical milling is gear-driven  
 ZX50F: vertical milling is belt-driven, swivel working table, steel sheet machine stand

**Standard accessories:**

Drill chuck, machine vice, draw bar, wrench, crank, work light, milling chuck set (8), 3-axis manual feed

**Optional accessories:**

3-axis DRO, H/V rotary table, universal dividing head, swivel work table (ZX50C), cast iron machine stand or steel sheet machine stand, 58pc clamping kit, mill chuck set (15), machine vise 160mm, X axis mechanical power feed, X, Y axis electric power feed, coolant system, CE spindle arbor "CE" spindle electrics.

Specifications	Unit	ZX50F	ZX50C
Max. drilling dia.	mm	50	50
Max. horizontal milling dia.	mm	100	100
Max. vertical milling dia.	mm	25	25
Max. boring dia.	mm	120	120
Max. tapping dia.	mm	M16	M16
Spindle taper	mm	MT4/ISO30	MT4/ISO30
Distance between spindle nose and table surface	mm	0-420	0-420
Spindle speed range	r.p.m	230-1825(8steps)	115-1750(8steps)
Spindle travel	mm	120	120
Table size	mm	800X240	800X240
Table travel	mm	400X230x380	400X230x380
Main motor	kw	0.85/1.5	0.85/1.5
N.W/G.W	kgs	500/600	500/600