

XZ6326B Drilling milling

Drilling milling machine



XZ6326B



XZ6326

Item No.	XZ6326	XZ6326B	XZ6326C
Specifications			
Table size	1120 x 260 mm		
Table travel (X,Y)	600 x 300 mm		
Knee travel	300 mm		
Table power feed speed range (X)	24 ~ 402 mm/min		
Table power feed speed range (Y)	24 ~ 402 mm/min		
Knee rapid speed	400 mm/min		
T-slot	3 x 14 – 63 mm		
Ram travel	700 mm		
Vertical Spindle:			
Distance spindle nose to table	115 – 430 mm		
Spindle taper	ISO40		
Spindle stroke	120 mm		
Step of spindle speeds	12		
Range of spindle speeds	67 ~ 2010 rpm		
Automatic spindle feed	0.1 / 0.15 / 0.3 mm/rev		
Spindle motor	1.5 / 2.2 kw		
Horizontal Spindle:			
Spindle taper	ISO40		
Step of spindle speeds	12		
Range of spindle speeds	38 ~ 1310 rpm		
Spindle motor	2.2 kw		
Distance spindle center to table	0 ~ 300 mm		
Distance Spindle center to ram	180 mm		
Packing size	1580x1450x2150mm		
Net weight	1350 kg		

Rectangular table guideway with high stability
Automatic spindle feed
Headstock lifting and lowering of headstock
Headstock swivel +45°
Hardened and ground table surface
XZ6236:X axis auto gear power feed
XZ6236B:X,Y axis Auto power feed
XZ6236C: X,Y axis Auto power feed,Z axis motor power feed.

Standard accessories:
Draw bar, spindle rod, reduction sleeve, wrenches, work lamp, coolant system, chip tray, horizontal cutter arbors.

Optional accessories:
DRO, universal dividing head, H/V worktable, 58pcs clamping kit, milling chuck set, "CE" standard electrics, CE spindle protecting arbor