



XZ6350Z Milling Drilling Machine

XZ6350Z/X6350ZB/XZ6350ZA/XZ6350ZS Milling & Drilling Machine

I Z: X Axis auto feed, with tapping

I ZA: X/Y Axis auto feed, with tapping

I ZB: X/Y Axis auto feed, Up/Down by motor on Z Axis, with tapping

I ZS: 3 Axis auto feed, speed adjustable on Z Axis, work table can be rotary to 45,with tapping.

Specifications	XZ6350Z	X6350ZB	XZ6350ZA	XZ6350ZS
Table size	1120x260 mm	1120x260 mm	1120x260 mm	1270x320 mm
Table travel (X,Y)	600x320 mm	600x260 mm	600x260 mm	730x270 mm
Knee travel	350 mm	330 mm	300 mm	400 mm
Table power feed speed range (X)	—	24 ~ 402 mm/min	24 ~ 402 mm/min	15 ~ 370 mm/min
Table power feed speed range (Y)	—	24 ~ 402 mm/min	24 ~ 402 mm/min	15 ~ 370 mm/min
Knee rapid speed	—	—	400 mm/min	575 mm/min
T-slot	3x14 - 63 mm		3x14 - 63 mm	
Ram travel	650mm	650mm	650mm	750 mm
Vertical Spindle:				
Distance spindle nose to table	100-430 mm			
Spindle taper	ISO40			
Spindle stroke	120 mm			
Step of spindle speeds	8			
Range of spindle speeds	90~2000 rpm			
Automatic spindle feed	0.08 0.15 0.25 mm/rev.			
Spindle motor	2.2 kw			
Head swivel (L&R)	± 45°			
Horizontal Spindle:				
Spindle taper	ISO40			
Step of spindle speeds	12			

Range of spindle speeds	38~1310 rpm			
Spindle motor	2.2 kw			
Distance spindle center to table	0 ~ 350 mm	0 ~ 330 mm	0 ~ 300 mm	0 ~ 360 mm
Distance Spindle center to ram	180 mm	180 mm	180 mm	250 mm
Packing size	1520×1285×2150 mm	1520×1290×2150 mm	1520×1290×2150 mm	1520×1285×2150 mm
Net weight	1350 kg	1400 kg	1400 kg	14350 kg