



UWF5 Universal swivel head milling machine

UWF5 Universal swivel head milling machine

Driven by servo motor

Table automatic feed on X Y Z

Automatic rapid feed on X Y Z

Table Swivel $\pm 45^\circ$

specifications		X6436VW	X6432VW	X6432BVW	X6430VW
Worktable size	Width (mm)	360	320	320	300
	Length (mm)	1325 /1600		1270/1370	
Worktable travel	Longitudinal (mm)	750/1300		720/820	
	Cross (mm)	320		300	
	Vertical (mm)	400		400	
Spindle taper		7:24 ISO50(V) 7:24 ISO50(H)		7:24 ISO40(V) 7:24 ISO40(H)	
Arm travel (mm)		550		400	
Distance between spindle nose and table surface (mm)		190-590		220-620	
Distance between horizontal nose and table surface (mm)		20-420		35-435	
Distance between spindle axis and arm surface (mm)		200		180	
Spindle speed (steps) (rpm)		60-1750 /12 (V) 60-1800/12 (H)		45-1660 /11 (V) 35-1500/12 (H)	
T- slot (Number/Width/Distance) (mm)		3/18/80	3/18/70	3/14/80	
Worktable swivel angle		$\pm 45^\circ$			
Main motor (Kw)		5.5 (V) 4 (H)		2.2 or 3 (V) 3 (H)	
Ac servo motor torque (X Y Z) (Nm)		10	10	10	

Overall size	Length (mm)	1800/2520		1720/1820	
	With (mm)	2100		1680	
	Hight (mm)	2000		1860	
Net weight (kg)		2685/2800	2635/2750	1875/1925	1850/1900