



X5646 Heavy duty Milling

| Specifications | Unit | X5646(UWF10) | X5750(UWF12B) | X5750(UWF15B) |
|---|--------|----------------------------------|-----------------------|-----------------------|
| Table size | mm | 460*1235 | 500*1600 | 500*2000 |
| T-slots(NO./width/pitch) | mm | 5*18*80 | | |
| Table travel (X/Y/Z) | mm | 900*450*650 | 1200*500*700 | 1500*500*700 |
| Swivel angle of milling head | - | 360° | | |
| Spindle taper | - | ISO40 | ISO50 | ISO50 |
| Spindle speed range | r.p.m | (27) 30-2050 | | |
| Table feed(X/Y/Z) | mm/min | 10-1000/10-1000/6-640 | 10-1000/10-1000/5-500 | 10-1000/10-1000/5-500 |
| Table rapid speed | | 2200/2200/1100 | | |
| Distance between spindle nose and table surface | mm | 32-482 | 25-525 | |
| Distance from spindle center line to column | mm | 47-697 | 55-755 | |
| Main motor power | Kw | 5.5 | 7.5 | |
| Feed motor | Kw | AC servo motor X/Y:15NM; Z: 18NM | | |
| Max load | Kg | 800 | 1800 | 1800 |
| Overall size | mm | 1835*2362*2090 | 2475*2260*2180 | 2986*2260*2180 |