



## XW5032A/XW5032B/XW5032C/VFM5 Vertical Milling Mach

Model No.	Units	XW5032A	XW5032B	XW5032C	VFM5
Specifications					
Table size	mm	1320x320			1600x320
Table travel (X,Y)	mm	750x300	750x300	1000x300	1300x320
Knee travel	mm	400			460
Table power feed speed range (X)	mm/min	20 ~ 360			30~730 (variable)
Table power feed speed range (Y)	mm/min	20 ~ 360			20~500 (variable)
Table power feed speed range (Z)	mm/min	-			15~375 (variable)
Knee rapid speed(Z)	mm/min	400			600
T-slot	mm	5x14-63			3x18-70
Distance from spindle nose to table	mm	45 ~ 445	35 ~ 435	35 ~ 435	50~500
Distance from spindle axis to column	mm	320	360	360	378
Spindle taper		ISO50			ISO50
Spindle stroke	mm	—	70	70	70
Step of spindle speeds		12			12
Range of spindle speeds	rpm	58 ~ 1710			50~1475
Head swivel		±35°			±30°
Spindle motor	kw	4			5.5
Overall dimension	mm	1770x1820x1880		2020x1820x1880	2294x2030x1900
Net weight	kg	2300	2300	2350	3000

## Vertical Knee- type Milling machine

Harden and ground guideways.  
 Rectangular table guideways with high sta  
 Spindle can feed,mill head can rotate  $\pm 35^\circ$   
 Automatic feeds on X,Y axis,motorized lifti  
 and lowering of table on Z axis

Standard accessories:  
 draw bar, spindle rod, reduction sleeve,  
 wrenches,  
 Parallel vice, mill chuck,drill chuck, work la  
 coolant system, titled wedge,horizontal cut  
 arbors

Optional accessories:  
 3 axis DRO,  
 Universal dividing head,  
 Rotary table,  
 58PCS clamping kit,  
 Mill chuck set (15),  
 Machine vise



Model No.	Units	XW5032A	XW5032B	XW5032C	VFM5
Specifications					
Table size	mm	1320 x 320		X6328A	1600 x 320
Table travel (X,Y)	mm	750 x 300	750 x 300	1000 x 300	1300 x 320
Knee travel	mm	400			460
Table power feed speed range (X)	mm/min	20 ~ 360			30~730 (variable)
Table power feed speed range (Y)	mm/min	20 ~ 360			20~500 (variable)
Table power feed speed range (Z)	mm/min	-			15~375 (variable)
Knee rapid speed(Z)	mm/min	400			600
T-slot	mm	5 x 14-63			3 x 18-70
Distance from spindle nose to table	mm	45 ~ 445	35 ~ 435	35 ~ 435	50~500
Distance from spindle axis to column	mm	320	360	360	378
Spindle taper		ISO50			ISO50
Spindle stroke	mm	-	70	70	70
Step of spindle speeds		12			12
Range of spindle speeds	rpm	58 ~ 1710			50~1475
Head swivel		$\pm 35^\circ$			$\pm 30^\circ$
Spindle motor	kw	4			5.5
Overall dimension	mm	1770 x 1820 x 1880	2020 x 1820 x 1880		2294 x 2030 x 1900
Net weight	kg	2300	2300	2350	3000