

ZJ5132 Bench type drilling machine

Drilling press bench type / floor type machine



ZJ4113

ZJ5125

ZJ5132

Feature:

- * Machine approved "CE" "EMC"
- * Normal drill chuck or quick-action drill chuck
- * High precision spindle
- * Big power motor
- * Overall control

Standard accessories:
drill chuck, chuck taper.

Optional accessories:
keyless chuck, machine vise.

Model	Unit	ZJ4113	ZJ4113A	ZJQ4116	ZJ4116	ZQJ4116A	ZQJ4116B	ZJQ5116
CAPACITY								
Drilling capacity(max.)	mm	φ 13	φ 13	φ 16	φ 16	φ 16	φ 16	φ 16
WORKING RANGE								
Sleeve travel	mm	50	50	85	85	85	85	85
SPINDLE								
Spindle taper		B16	B16	MT2	MT2	B16	MT2	MT2
SPEEDS								
Spindle speeds(50HZ)	rpm	580-2650	580-2650	180-2770/220-3320	180-2770/220-3320	420-2640	300-2550/360-3060	180-2770/220-3320
Number of steps	speed	5	5	16	16	9	12	16
DRILLING TABLE								
Table size	mm	160x160	160x160	φ 290	290x290	170x170	φ 260	φ 290
Base size	mm	290x190	340x210	420x250	460x272	315x195	420x250	460x272
Column diameter	mm	φ 46	φ 58	φ 72	φ 72	φ 46	φ 58	φ 72
Height	mm	580	680	980	1000	610	900	1580
ELECTRIC SUPPLY								
Motor	W	250/350	450	375/450/550	450/550	500	375/450	450/550
DIMENSIONS AND WEIGHT								
packing size(LxWxH)	mm	440x340x220	570x410x265	780x450x280	825x490x290	465x355x225	780x495x280	1140x460x280
Net weight/Gross weight	kgs	19/20	27/29	50/52	60/63	24/26	40/42	60/63
Quantity/20' container	Pcs	900	450	310	250	850	310	200

Model	Unit	ZJ5116	ZJQ4120	ZJ4120	ZJQ5125	ZJ5125	ZQJ5132	ZJ5132
CAPACITY								
Drilling capacity(max.)	mm	φ 16	φ 20	φ 20	φ 25	φ 25	φ 32	φ 32
WORKING RANGE								
Sleeve travel	mm	85	85	85	85	120	120	120
SPINDLE								
Spindle taper		B16	MT2	MT2	MT3	MT3	MT4	MT4
SPEEDS								
Spindle speeds(50HZ)	rpm	180-2770/220-3320	180-2770/220-3320	180-2770/220-3320	280-2380/340-2860	150-2450/180-2940	150-2450/180-2940	150-2450/180-2940
Number of steps	speed	16	16	16	12	12	12	12
DRILLING TABLE								
Table size	mm	290x290	250x250	290x290	290x290	350x350	360X360	480X420
Base size	mm	460x272	420x250	460x272	460x272	500x375	500x375	560x450
Column diameter	mm	φ 72	φ 72	φ 72	φ 80	φ 92	φ 92	φ 92
Height	mm	1600	1200	1200	1600	1710	1710	1710
ELECTRIC SUPPLY								
Motor	W	450/550	450	550/750	750	1100/1500	1100	1100
DIMENSIONS AND WEIGHT								
packing size(LxWxH)	mm	1140x500x300	1010x490x280	1010x490x280	1140x500x300	1430x670x330	1430x670x330	1430x670x330
Net weight/Gross weight	kgs	70/74	51/53	63/66	80/84	120/128	130/138	145/153
Quantity/20' container	Pcs	180	200	200	180	86	86	86