

## ZY5025A / ZY5030A/ ZY5032A / ZY5035A / ZY5040A / Z

## **FEATURE**:

3-phase with two-voltage for 220V~575V collocation

All main parts are made with quality cast iron

Single-speed motor, 12 step gear shift

Unload tool device and coolant, fender device

Strength spindle, large diameter column

Worktable could be rotated and could be inclined  $\pm 45^{\circ}$ 

Motor driven lifting of worktable.

Digital readout the display of speed and cutting depth for drilling diameter above 35mm(including 35mm)

ZY5035B/ZY503 ZY5040B/ZY5040 ZY5050B/ZY5050

Micro feed is available.

Trochoid thin oil lubrication

Superior quality of gears with hardened and lapped gears of surface

Main motor with break.

Importable electrical components with CE,CSA and UL standard

The model with A is electromagnetism clutch transmission feed, with B is mechanical feed.

Model	5A	A	A
Max. drilling diameter (steel) and tapping diameter	Ø35mm / M22m m	Ø40mm / M24m m	Ø50mm / M30m m
Max. milling cutter diameter	80mm	80mm	80mm
Max. travel of spindle	190mm	200mm	240mm
Max. distance from spindle to generating line of colum n	340mm	360mm	360mm
Max. distance from spindle nose to the worktable surf ace	665mm	590mm	590mm
Max. distance from spindle nose to the surface of bas e worktable	1195mm	1175mm	1170mm
Max. travel of worktable and bracket / Manual (Mecha nical)	570mm/450mm	530mm / 410mm	530mm / 410mm
Swivel angle of worktable	±45°	±45°	±45°
Spindle taper bore	MT4	MT4	MT4
Spindle speed steps	12	12	12

Spindle speed range	76~2065r/min	52~1400r/min	52~1400r/min
Spindle feed steps	3	4	4
Spindle feed range	0.1, 0.2, 0.3mm/ r	0.1, 0.2, 0.3, 0.4 mm/r	0.1, 0.2, 0.3, 0.4 mm/r
Dimension of worktable	520mm×440mm	580mm×460mm	580mm×460mm
Effective working area of worktable	405mm×395mm	445mm×435mm	445mm×435mm
Diameter of column	Ø140mm	Ø160mm	Ø180mm
Power of motor	1.5kw	2.2kw	3kw
Machine dimension	849×545×2290 mm	940×680×2405m m	950×680×2405m m
Packing dimension	1000×650×2220 mm	1170×680×2300 mm	1170×680×2300 mm
Net weight and gross weight	565kg / 615kg	620kg / 675kg	655kg / 710kg
Sets/ 20'container	20	16	16