



Z3032X10/1,Z3040X10/1,Z3040X13/1

With wide range of speed and feed , with manual, power and fine feeds . the feed of machines are very easily engaged and disengaged at any time.

With safe and reliable feed safety machine, all parts easy operation and change .

All controls centralized on the head stock easy operation and change. Clamping for assemblies and speed change of spindle achieved by hydraulic power.

Main parts are made by machine center which import form KIA with high precision and efficiency, ensuring reliability and high quality.

Integrating technology for casting parts is excellent, adopting casting equipment, ensuring high quality of material for basic parts.

Spindle parts are made by special high quality steel heat treatment to be made by first class equipments, ensuring high strength and durability.

Main gears are machined by gear grinding , the machine ensuring high precision and low noise.

SPECIFICATION		Z3032X10/1 Z3040X10/1	Z3040X13/1
Max. drilling capacity	mm	32/40	40
distance spindle axis to column generating line	mm	300-1000	300-1300
diameter of column	mm	240	300
Spindle taper		MT4	MT4
Spindle travel	mm	280	280
Spindle speeds range	r/min	32-2500	32-2500
Spindle speeds series		16	16
Range of spindle feeds	mm/r	0.10-1.25	0.10-1.25
Spindle feeds		8	8
Distance spindle nose to working surface of base	mm	220-1000	300-1320
Dimension of worktable	mm	600*450*450	600*450*450
Dimension of base	mm	1710*800*160	2050*900*200
Overall size	Mm	1760*800*2050	2100*900*2300
Power of main motor	Kw	2.2	3
G.W/ N.W	kg	1920/1830	2500/2100
Packing dimension	cm	187*97*220	235*106*245