



## Z3050X12/1

With wide range of speed and feed , with manual, power and fine feeds . the feed of machines are very easily engaged and disengaged at any time.

With safe and reliable feed safety machine, all parts easy operation and change .

All controls centralized on the head stock easy operation and change. Clamping for assemblies and speed change of spindle achieved by hydraulic power.

Main parts are made by machine center which import form KIA with high precision and efficiency, ensuring reliability and high quality.

Integrating technology for casting parts is excellent, adopting casting equipment, ensuring high quality of material for basic parts.

Spindle parts are made by special high quality steel heat treatment to be made by first class equipments, ensuring high strength and durability.

Main gears are machined by gear grinding , the machine ensuring high precision and low noise.

<b>SPECIFICATION</b>		Z3050X12/1
Max. drilling capacity	mm	50
distance spindle axis to column generating line	mm	350-1250
diameter of column	mm	350
Spindle taper		MT5
Spindle travel	mm	315
Spindle speeds range	r/min	25-2000
Spindle speeds series		16
Range of spindle feeds	mm/r	0.04-3.2
Spindle feeds		16
Distance spindle nose to working surface of base	mm	350-1220
Dimension of worktable	mm	630*500*500
Dimension of base	mm	2050*1000*200
Overall size	Mm	2150*1060*2650
Power of main motor	Kw	4
G.W/ N.W	kg	3250/3000
Packing dimension	cm	240*112*252