



## CQ6125V Lathe

Feature :			
·Precision ground and supersonic frequency hardened bed ways.It features with high accuracy and well wear-resisting.			
·The spindle is supported with precision roller bearing.			
·Safety magnetic switch or lock key switch.			
·The spindle bore is 26mm.			
·Variable control for quick spindle speed changing.			
PRECISION&VARIABLE SPEED BENCH LATHE	CQ6125V		
Model	CQ6125Vx400	CQ6125Vx550	CQ6125Vx750
Distance between centers	400mm	550mm	750mm
Max. swing over bed	Φ250mm		
Max. swing over cross slide	Φ150mm		
Width of bed	135mm		
Taper of spindle bore	M.T.#4		
Spindle bore	Φ26mm		
Range of spindle speeds	125---2000rpm		
Range of longitudinal feeds	0.07-0.20mm/rev		
Inch threads can be cut	8-56 T.P.I		
Metric threads can be cut	0.4-3.5mm		
Max. travel of top slide	70mm		

Max. travel of cross slide	115mm		
Max. travel of tailstock quill	65mm		
Taper of tailstock quill	M.T.#2		
Motor power	750W (DC. motor)		
Packing size	1045mm×560mm×565mm	1155mm×560mm×565mm	1355mm×560mm×565mm
N.W	105kg	109kg	119kg
G.W	145kg	149kg	159kg
Foot stands(L×W×H)	500mm×300mm×750mm		
Foot stands (N.W)	44kg		
Foot stands (G.W)	48kg		
<b>Stand Accessories :</b>		<b>Optional Accessories :</b>	
·3-Jaw Chuck		·4-Jaw Chuck	
·Change Gears Set		·Face Plate	
·Tool Box and Tools		·Steady Rest	
·Dead Centers		·Follow Rest	
		·Live Center	
		·Turning Tool Set·	
		Splash Guard	
		·Oil Tray	
		·Foot Stands	
		·Leadscrew Guard	
		·Chuck Guard	
		·Drill Chuck+Drill Arbor	