



## CQ6128 Lathe

**Feature:**

- Precision ground and supersonic frequency hardened bed ways. It features with high accuracy and well-resisting.
- The spindle is supported with precision roller bearing.
- Safety magnetic switch or lock key switch .The width of bed ways is up to 180mm, providing superbridity.

PRECISION&POWERFUL BENCH LATHE	C6128	C6128V
Model	C6128x610	C6128Vx610
Max. swing over bed	Φ280mm	
Max. swing over cross slide	Φ150mm	
Distance between centers	610mm	
Width of bed	180mm	
Spindle bore	Φ26mm	
Taper of spindle bore	M.T.#4	
Range of spindle speeds	125-2000rpm	0-2500rpm(Variable speed)
Taper of tailstock quill	M.T.#3	
Metric threads can be cut	0.1-3.5mm	
Inch threads can be cut	8-35TPI	
Range of longitudinal feeds	0.1-0.25mm/rev	
Max. travel of cross slide	110mm	
Max. travel of top slide	70mm	
Max.travel of tailstock quill	80mm	
Motor power	750w	1.0kw
Packing size(L*W*H)	1320mm×650mm×610mm	

N.W/G.W	218kg/258kg
Foot stands(L*W*H)	280mm×390mm×600mm
Foot stands(N.W/G.W)	52kg/56kg
<b>Stand Accessories :</b>	<b>Optional Accessories :</b>
·3-Jaw Chuck	·4-Jaw Chuck
·Change Gears Set	·Face Plate
·Tool Box and Tools	·Steady Rest
·Dead Centers	·Follow Rest
	·Live Center
	·Turning Tool Set·
	Splash Guard
	·Oil Tray
	·Foot Stands
	·Leadscrew Guard
	·Chuck Guard
	·Drill Chuck+Drill Arbor