

T806, T807, T808, T8014A, T8016A

Cylinder boring machine T806 T807 T806A T808A T8014A T8016A

The boring machine is mainly used for reboring engine cylinders of motor cycles, automobiles and middle & small- tractors.

MODEL	T806	T807	T806A	T808A	T8014A	T8016A
Boring diameter	Φ39-Φ60mm	Φ39-Φ70mm	Φ40-Φ80mm	Φ50-Φ85mm	Φ65-Φ140mm	Φ80-Φ165mm
Max.boring depth	160mm	160mm	160mm	170mm	300mm	400mm
Spindle speed	486 r/min	486 r/min	486 r/min	394 r/min	250,380 r/min	200, 300 r/min
Spindle feed	0.09 mm/r	0.09 mm/r	0.09 mm/r	0.1 mm/r	0.11 mm/r	0.12 mm/r
Spindle quick reset	manual	manual	manual	manual	636 mm/min	780 mm/min
Voltage	220V / 380V	220V / 380V	220V / 380V	220V / 380V	220V / 380V	220V / 380V
Motor Output	0.25kw	0.25kw	0.25kw	0.25kw	0.25/0.37kw	0.25/0.37kw
Motor speed	1440 r/min	1440 r/min	1440 r/min	1440 r/min	1440 r/min	1440 r/min
Overall dimensions	330x400x1080 mm	330x400x1080 mm	330x400x1080 mm	350x272x725 mm	320x330x850 mm	360x345x1100 mm
Machine weight	80kg	80kg	80kg	48kg	62kg	85kg