



## TXM-170A TXM-200A TXM-250A Vertical Fine Boring & Specifications

ITEMS			TXM-170A	TXM-200A	TXM-250A
Max. boring diameter	Mm		φ170	φ200	φ250
Max. boring depth	Mm		400	500	500
Max. grinding area	Mm		400 X 1000		
Max.milling area	Mm		400x1000		
Max. drilling& reaming diameter	Mm		φ30		
Spindle speed	r/min		120-860		
Feeding of the spindle	Mm/min		14-900		
Rapid moving speed of the spindle	Mm/mim		900		
Spindle travel	Mm		700		
Distance between spindle end face and table	Mm		0-700		
Distance between spindle axis and carriage vertical plane	Mm		375		
Longitudinal feed of worktable	Mm/mim		32-1350		
Rapid moving speed of the table longitudinal travel	Mm/mim		1350		
Max. longitudinal travel of the working table	Mm		1500		
Max. cross travel of the working table	Mm		200		
Worktable size(W*L)	Mm		500*1250	500*1500	500*1500
Processing roughness	Boring		Ra2.5		
	Milling	Mm	Ra3.2		
	Grinding		Ra0.8		
Main motor power	Kw		5.5		
Overall dimensions (L*W*H)	Cm		260*163*230		
Packing dimensions(L*W*H)	Cm		223*187*227		
N.W./G..W.	kg		3300/3600	3500/3800	3500/3800
Remark			Accessories refer to accessories list of boring machine		