



CK6132/450 CNC

The machine can process precisely internal or external diameter, face, taper, arc and threading with high efficiency

Standard toolpost is 4-stations, also 6-stations toolpost can be optional selection

Spindle speed changed by frequency

Induction harden bed-

way. Bed saddle with plastic sticker can improve the accuracy and service life of the machine

The spindle is supported by imported precision bearings

Normally machine is provided with 3-

jaw chuck. According to customer's optional selection, hydraulic chuck or pneumatic chuck also can be supplied.

ITEM	CK6132/450	
Swing over bed	Φ 320mm	
Swing over camiage	Φ 150mm	
Distance between centers	750mm	1000mm
Taper of barrel	M. T. 5	
Spindle hole	Φ 38mm	
Range of speed(variable)	100~2500r/min	
Feed motor power(X/Z)	6N. M/12N. M(Step motor)	
X rapid traverse	5m/min	
Z rapid traverse	10m/min	
Max. travel of X axis	160mm	
Max. travel of Z axis	450mm	
Motor power	2.2Kw	
Tool-post	4 stations or 6 stations	
Max. tool size	16× 16mm	
Min input unit	0.001mm	
repeatability accuracy(X/Y)	0.01mm	
Barrel travel of tailstock	160mm	
Barrel taper of tailstock	M. T. 3	
Packing size(L× W× H)	1820× 1100× 1650mm	
N/G Weight	1000/1200kg	

Especificaciones

De metal de trabajo herramientas torno cnc ck6132

1. el certificado del ce 2. schneiderinterruptor 3. calidad de cambiar el mundo 4. fanuc de siemens
de metal de trabajo herramientas torno cnc ck6132

1. modelo: ck6132

2. de la marca: taian haishu

3. dia. 3-jaw de chuck: 160mm

4. chuck tipo: manual de, hidráulico, neumático

5. taistock tipo: manual de, hidráulico, neumático

los artículos	especificaciones
Max. Nadar sobre la cama	Φ 320mm
Max. Nadar sobre el carro	Φ 160mm
Max. La longitud de la pieza de trabajo	450mm
rango de velocidad del husillo	100-2500rpm
eje de diámetro	Φ 38mm
de la forma cónica del huso diámetro	mt5
las estaciones de portador de herramienta	4/6/o pandillas- tipo de herramienta del portador
Min. El establecimiento de la unidad de motor eléctrico	(z) 0.001mm largo,(x) cross0.001mm
velocidad de movimiento de post	(z) long 8 m/min,(x) 6 cruz m/min
de la forma cónica de taikstock canilla	mt3
Max. Gama de caña del contrapunto	100mm
potencia del motor	4kw

2,características principales

- **De alta- speed precise main spindle**
- **precise tornillo de la bola**
- **the repeated positioning accuracy shall be within 0.012mm**
- **Design in integral high rigidity**
- **Bundant function options**
- **Perfect mechanism design**
- **Quick clamping and loosening mechanism of main spindle**
- **Abundant optional configuration**