



## CQ6232E Lathe

Technical data	
Distance between centers	880mm      1000 mm
Swing over bed	320 mm
Swing over carriage	198 mm
Swing over gap	450 mm
Spindle taper	MT 5
Spindle bore	38 mm
Range of spindle speed	70 - 2000 r/min / 8 steps
Compound rest travel	80 mm
Cross slide travel	160 mm
Longitudinal feed rates	0,079 - 1,291 mm/r / 36 steps
Cross feed rates	0,017 - 0,276 mm/r / 36 steps
Metric threads	0,4 - 7,0 1/mm / 36 kinds
Whitworth threads	4 - 60 T.P.I. / 36 kinds
Tailstock barrel taper	MT 3
Tailstock barrel stroke	100 mm
Motor	1500 W / 230 V
Dimensions	1850 x 750 x 1400 mm
Weight	560 kg

Standard accessories	Optional accessories
3-jaws chuck	Drill chuck with arbor
4-jaws chuck	Quick change tool post
Compound rest + tool post	Lead screw cover
Dead centers	Coolant system
Change gears	Foot brake

<b>Steady rest</b>	<b>2 axis DRO</b>
<b>Follow rest</b>	
<b>Machine base</b>	
<b>Splash guard</b>	
<b>Face plate</b>	
<b>Work lamp</b>	
<b>Tool kit</b>	

**Available with 880 mm center distance as well.**